



DAIKIN ONE LITE CONNECTED THERMOSTAT

Description

The Daikin ONE lite connected thermostat is a perfect solution for Daikin single and multi-zone products when a wall-mounted smart thermostat is needed. The Daikin ONE lite connected thermostat is compatible with most Daikin single and multi-zone systems and can be linked via Wi-Fi to the *SkyportHome* app for control.

Standard Features

- Compact, non-intrusive design suitable for most interior environments
- Multifunction push buttons labeled for mode, fan, set-point up, set-point down
- Wi-Fi-enabled connected thermostat that works with *SkyportHome* app (iOS and Android)
- Voice control by Amazon Alexa and Google Assistant
- Programmable schedule
- Built-in temperature and humidity sensors
- Indoor unit Control: Mode (Auto/Heat/Cool/ Emergency Heat), Setpoint (Dual/Single), Fan Speed, Fan On/Auto (with minimum run time)
- LED Mode indicator for heating and cooling
- Dehumidification function (setup with *SkyportCare* app)
- Error and maintenance notifications
- Control and comfort functions: Away mode and geo-fencing
- Over-the-air software update capable (requires Wi-Fi connection)
- Compatible with *SkyportCare*
- Setup is possible within the *SkyportCare* app via the *Quality Install* tool.



Ductless Mini & Multi-Split Systems	Type	Compatible Family (Models starting with)
	R-410A S21 Indoor Units ¹	CDXS, CTXS ² , FDXS, FTK ² , FTXB ² , FTXF ² , FTXG ² , FTX09_12N ² , FTX15_18_24N ³ , FTXR, FTXS, FVXS ³

¹ Must Install with provided Communication Adaptor DAPT-ONE-S21

² Must purchase S21 adaptor KRP067A41E

³ Must purchase S21 adaptor KRP980B2E

⁴ The Sarara drying function of the QUATERNITY units is not supported with Daikin ONE lite connected thermostat, but the dehumidification function of the Daikin ONE lite can be used with the QUATERNITY indoor units

Technical Specifications

- Backlit, 3.5 inch MVA TFT LCD display
- Bi-directional communications protocol for controlling HVAC system
- Multi-language support: English, Spanish, French (*SkyportCare* app only)
- 1 Auxiliary Heat output (dry contact), configurable as a primary or secondary heat source for heat pump systems only.
- Includes Translation adaptor for S21 systems. (Note this control is not for use with P1P2 systems).
- FCC Certified/UL Listed
- An optional trim plate (PSPAC-WPM-L) is available.

Product Dimensions

- 3.3" W x 3.3" H x 1.04" D

Product Number

- DTST-LTE-LA-A



* Complete warranty available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California, Florida, or Québec. The duration of warranty coverages in Texas and Florida differs in some cases. Other limitations and exclusions apply, refer to complete warranty details for full list of limitations and exclusions.

¹ 12-Year Limited Warranty is available for owner-occupied residences only.

For multi-family and/or commercial applications, the warranty period is 5-years.

Google, Google Assistant, and all related logos are trademarks of Google, or its affiliates. Amazon, Alexa, and all related logos are trademarks of Amazon.com, Inc. or its affiliates.

Our continuing commitment to quality products may mean a change in specifications without notice.
©2025 DAIKIN COMFORT TECHNOLOGIES MANUFACTURING, INC. • Houston, Texas • Printed in the USA.