

**DAIKIN ONE+ and ONE TOUCH HOMEOWNER SETTINGS MENU OUTLINE**  
(based on v3.9 software for VRV and mini/multi-split systems)

Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7
home screen	mode icon	(see below)				
	room relative humidity					
	room temperature					
	csp and cooler/down icon					
	hsp and warmer/up icon					
	thermostat name field					
	critical error messages	(if any)				
	status messages					
schedule screen	(see below)					
away screen	away csp and hsp					
air quality screen	room temperature					
	outdoor temp					
	outdoor humidity					
	weather forecast					
	circulate air (selection)	off on				
	fan	(same options as fan menu below)				
	system mode	auto (cool & heat) -or- master controlled	(The "master controlled" option appears only for VRV systems, and only if another thermostat is master.)			
		cool				
		heat				
		off				
		emergency heat	(if aux heat source available)			
	fan	cooling fan speed	auto	(depends on indoor unit)		
			low	(depends on indoor unit)		
			medium low	(depends on indoor unit)		
			medium	(depends on indoor unit)		
			medium high	(depends on indoor unit)		
		cooling vertical position	high	(depends on indoor unit)		
			oscillate	(depends on indoor unit)		
			fixed	(depends on indoor unit)		
		cooling horizontal position	position	(only VRV, depends on indoor unit)		
			oscillate	(depends on indoor unit)		
		heating fan speed	fixed	(depends on indoor unit)		
			auto	(depends on indoor unit)		
			low	(depends on indoor unit)		
			medium low	(depends on indoor unit)		
			medium	(depends on indoor unit)		
			medium high	(depends on indoor unit)		
		heating vertical position	high	(depends on indoor unit)		
			oscillate	(depends on indoor unit)		
			fixed	(depends on indoor unit)		
		heating horizontal position	position	(only VRV, depends on indoor unit)		
			oscillate	(depends on indoor unit)		
	schedule	paused until...	fixed	(depends on indoor unit)		
			on			
			off			
		edit schedule (appears when schedule on)	(if schedule paused)			
				(1st schedule event name)	day (weekday of event)	
					time	(time selection)
					label	(text entry)
					action	set temperature
					temperature	(selection of heat and cool setpoints)
			Sunday Monday Tuesday Wednesday Thursday Friday Saturday	(2nd schedule event name) start time heat setpoint/cool setpoint (up to 6 schedule events) copy day add event	(same options as 1st schedule event)	
		override duration (appears when schedule on)	until next event			
			for one hour			
			for two hours			
			for four hours			
			for eight hours			
	away	on (radio button)				
		off (radio button)				
		away temperatures	(selection of heat and cool setpoints)			
		receive geofencing events (checkbox)				
	display	language	english			
			español			
		degree units	française			
			fahrenheit			
		brightness	celsius			
			50 - 100% scale			
		night mode	night mode (check box)			
			from (time selection) to (time selection)			
		use large font (check box)				
		use light bar (check box)				
		screen saver	off			
			blank screen			
			analog clock			
	sound	digital clock				
		screen cleaning	touch screen is disabled for cleaning (30s)			
		lock	Enter a 4-digit PIN...	(number entry)		
	sound	use sound (check box)	(not on the Touch thermostat)			
			Off			

reminders	(list of installed filters with reminders menu for each)	1 month			
		2 months			
		3 months			
		4 months			
		6 months			
		12 months			
		restart timer	cancel		
date & time	time zone	(list of North America time zones with radio button selection)			
	month/date/year	(selection with spinner, for display only if connected to internet)			
	hour/minute/am or pm	(selection with spinner, for display only if connected to internet)			
	use 24-hour time format (checkbox)				
wifi	use wifi (checkbox)				
	networks (current network)	network list	legal notices	terms of use (text)	
				privacy policy (text)	
				end user license agreement (text)	
				decline	
				accept	
			(password text box)	(if protected network)	
			show password (checkbox)		
			advanced settings	use dhcp (checkbox)	(screen appears after legal notices accepted)
			connect per agreed terms (and) Done	(initiates connection to wifi network)	
	searching for networks (or) search again				
	internet connected (check)				
	Daikin One Cloud connected (check)				
	legal notices	terms of use	(text)		
		privacy policy	(text)		
		end user license agreement	(text)		
	restart thermostat (if internet but no cloud)				
	(6-digit account code if app not connected)				
account	(account email if app connected)				
	reset registration (if app connected)	cancel			
		continue			
air quality	circulate air	off			
		on			
humidity	target humidity	humidify if less than (25% - 65%)	(5% increments)		
		dehumidify if more than (35% - 75%)	(5% increments)		
	overcool to dehumidify	Overcooling allowed to dehumidify: 0°F to 3°F (0°C to 1.5°C)	(1°F or 0.5°C increments)		
		Temperature setpoint deadband: 2°F to 9°F (1°C to 5°C)	(1°F or 0.5°C increments)		
energy	demand response	use demand response (checkbox)	(only functional with local utility support)		
		When demand response signal is received:	offset temperature setpoints		
			use fixed temperature setpoints		
		response settings	setpoint offsets	Offset heat setpoints by this value: (-1°F to -7°F)	
				Offset cool setpoints by this value: (1°F to 7°F)	
			event setpoint limits	(50°F to 90°F)	
thermostat	name	main room			
		upstairs			
		downstairs			
		hallway			
		bedroom			
		kitchen			
		other			
		other name (if other selected)	(text entry)		
	model ONEPLUS				
	software version (x.x.x format)				
	wifi address (x:x:x:x:x format)				
	thermostat ID (DKN...)	(2D barcode of DKN number for cloud commissioning)			
equipment	indoor unit	dismiss			
		cancel			
		continue			
		software update found (or) no update available--dismiss			
	outdoor unit	COMMUNICATING EQUIPMENT:			
		(unit description)			
		model #			
		serial #			
	remote sensors	unit type			
		(unit description)			
		model #			
		serial #			
	ADDITIONAL EQUIPMENT:	include thermostat (temp/hum values)	(check box)		
		(sensor name) (temp/hum values)	sensor name	(text entry)	
			sensor type	surface mount	
			signal strength (acceptable, marginal, or low)	(bar displaying signal strength)	
			cancel		

				save		
			(sensor name) (temp/hum values)	(similar, up to 8 sensors)		
		air quality sensor	(if installed)			
		aux heat source	(if installed)			
		filter box	(if installed)			
		HEPA filter	(if installed)			
		standard filter	(if installed)			
		dehumidifier	(if installed)			
		humidifier	(if installed)			
		VRV IDU sensor	(only VRV systems, if installed)			
	support	Daikin Support				
		Daikin Dealer				
		cloud services	no access			
			view only			
			adjust settings			
	dealer edit	cancel	(i)	(4 digit pin for thermostat)		
		continue	4 digit code (text entry)			
			unlock thermostat (or) done	(entry into commissioning screens)		